PUBLIC HEALTH SERVICE U.S. FOOD AND DRUG ADMINISTRATION OFFICE OF FOOD SAFETY SHELLFISH AND AQUACULTURE POLICY BRANCH 5100 PAINT BRANCH PARKWAY COLLEGE PARK, MD 20740-3835 TEL. 240- 402-2151/2055/4960 FAX 301-436-2601							
SHELLFISH LABORATORY:	I LABORATORY EV	ALUATION C	HECKLIST				
ADDRESS:							
TELEPHONE:	FAX:						
EMAIL:							
DATE OF EVALUATION:	DATE OF REPORT	:	LAST EVALUATION:				
LABORATORY REPRESENTED BY	:	TITLE:					
LABORATORY EVALUATION OFF	ICER:	SHELLFISH S REGION:	PECIALIST:				
OTHER OFFICIALS PRESENT:		TITLE:					
Items which do not conform are noted C- Critical K - Key O - Other NA	by: Co A- Not Applicable	onformity it not	ed by a "√"				
Check the applicable analytical method	ls:						
Multiple Tube Fermentation Te							
Multiple Tube Fermentation Te	-	-	.RT II]				
Membrane Filtration Techniqu							
Multiple Tube Fermentation To		Meats (APHA)[I	PART III]				
Standard Plate Count for Shell		110 1 3 4					
Elevated Temperature Coliforn							
Male Specific Coliphage for So	oft-shelled Clams and A	American Oyster	s [PART III]				

CODE	REF.			ITEM				
K	8, 11	1.1 Quality Assurance (QA) Plan						
			1.1.1	Written Plan (Check those items which apply.)				
				a. Organization of the laboratory.				
				b. Staff training requirements.				
				c. Standard operating procedures.				
				d. Internal quality control measures for equipment, their calibration, maintenance, repair, performance, and rejection criteria established.				
				e. Laboratory safety.				
				f. Internal performance assessment.				
				g. External performance assessment.				
С	8	Ē	1.1.2	QA Plan Implemented.				
K	11		1.1.3	The Laboratory participates in a proficiency testing program annually. Specify Program(s)				
		1.2 Ed	lucation	al/Experience Requirements				
С	State's Human Resources Department		1.2.1	In state/county laboratories, the supervisor meets the state/county educational and experience requirements for managing a public health laboratory.				
К	State's Human Resources Department		1.2.2	In state/county laboratories, the analyst(s) meets the state/county educational a experience requirements for processing samples in a public health laboratory.				
С	USDA Microbiology & EELAP		1.2.3	In commercial laboratories, the supervisor must have at least a bachelor's degree or equivalent in microbiology, biology, or equivalent discipline with at least two years of laboratory experience.				
K	USDA Microbiology & EELAP		1.2.4	In commercial laboratories, the analyst(s) must have at least a high school diploma and shall have at least three months of experience in laboratory sciences.				
		1.3 W	ork Ar	ea				
0	8,11		1.3.1	Adequate for workload and storage.				
K	11		1.3.2	Clean, well-lighted.				
K	11	Ē	1.3.3	Adequate temperature control.				
0	11	Ħ	1.3.4	All work surfaces are nonporous, easily cleaned and disinfected.				
K	11	đ	1.3.5	Microbiological quality of the air is fewer than 15 colonies for a 15 minute exposure and determined monthly. The results are recorded and records maintained.				
		1.4 La	borato	y Equipment				
0	9		1.4.1	To determine the pH of prepared media, the pH meter has a standard accuracy 0.1 units.				
0	14		1.4.2	pH electrodes consisting of pH half-cell and reference half-cell or equivalent combination electrode free from (Ag/AgCl) or contains an ion exchange barrie preventing passage of Ag ions into the medium which may affect the accuracy of the pH reading.				
K	11		1.4.3	The effect of temperature on the pH is compensated for by an ATC probe or by manual adjustment.				
K	8		1.4.4	pH meter is calibrated daily or with each use Results are recorded and records maintained.				
K	11		1.4.5	A minimum of two standard buffer solutions is used to calibrate the pH meter. The first must be near the electrode isopotential point (pH 7). The second near				

			used once and discarded.
0	8,15	1.4.6	Electrode acceptability is determined daily or with each use by the millivolt
			procedure or through determination of the slope. (Circle the method used.)
K	9	1.4.7	Balance provides a sensitivity of at least 0.1 g at weights of use.
К	11,13	1.4.8	Balance calibrations are checked monthly according to manufacturer's specifications using NIST Class S or ASTM Class 1 or 2 weights or equivalent. The accuracy of the balance is verified at the weight range of use. Results are recorded and records maintained.
K	11	1.4.9	Refrigerator temperature(s) are monitored at least once daily on workdays Results are recorded and records maintained.
K	1	1.4.10	Refrigerator temperature is maintained at 0 to 4°C.
С	9	1.4.11	The temperature of the incubator is maintained at 35 ± 0.5 °C.
С	11	1.4.12	Thermometers used in the air incubator(s) are graduated in at least 0.1°C increments.
K	9	1.4.13	Working thermometers are located on top and bottom shelves or appropriately placed based on the results of spatial temperature checks.
С	11	1.4.14	Temperature of the waterbath is maintained at 44.5 ± 0.2 °C under all loading conditions.
С	9	1.4.15	The thermometers used in the waterbath are graduated in at least 0.1°C increments.
С	13	1.4.16	The waterbath has adequate capacity for workload.
K	9	1.4.17	The level of water in the waterbath covers the level of liquid in the incubating tubes.
K	8, 11	1.4.18	Air incubator/waterbath temperatures are taken twice daily on workdays. The results are recorded and records maintained.
С	4	1.4.19	All working thermometers are appropriately immersed.
С	29	1.4.20	Working thermometers are either: calibrated mercury-in-glass thermometers, calibrated non-mercury-in-glass thermometers, or appropriately calibrated electronic devices, including Resistance Temperature Devises (RTDs) and Platinum Resistance Devices (PTDs).
С	11	1.4.21	A mercury-in-glass standards thermometer has been calibrated by NIST or a qualified calibration laboratory using a primary standard traceable to NIST or an equivalent authority at the points 0, 35 and 44.5°C (45.5°C for
K			
ĸ	9	1.4.22	ETCP). These calibration records are maintained. Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained.
C	9 29	1.4.22 1.4.23	 ETCP). These calibration records are maintained. Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained. Date of most recent determination Either mercury-in-glass thermometers, non-mercury-in-glass thermometers having the accuracy (uncertainty), tolerance and response time of mercury or low drift electronic resistance thermometers with an accuracy of ≤ ±0.05°C are used as the laboratory standards thermometer. (<i>Circle the</i>
			 ETCP). These calibration records are maintained. Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained. Date of most recent determination Either mercury-in-glass thermometers, non-mercury-in-glass thermometers having the accuracy (uncertainty), tolerance and response time of mercury or low drift electronic resistance thermometers with an accuracy of ≤ ±0.05°C are used as the laboratory standards thermometer. (<i>Circle the thermometer type used.</i>)
С	29	1.4.23	 ETCP). These calibration records are maintained. Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained. Date of most recent determination Either mercury-in-glass thermometers, non-mercury-in-glass thermometers having the accuracy (uncertainty), tolerance and response time of mercury or low drift electronic resistance thermometers with an accuracy of ≤ ±0.05°C are used as the laboratory standards thermometer. (<i>Circle the thermometer type used.</i>) Incubator and waterbath working thermometers are checked annually against the standards thermometer at the temperatures at which they are used. Results are
C K	29 13	1.4.23 1.4.24 1.4.25	 ETCP). These calibration records are maintained. Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained. Date of most recent determination
C K	29 13	1.4.23 1.4.24 1.4.25	 ETCP). These calibration records are maintained. Standards thermometers are checked annually for accuracy by ice point determination. Results recorded and maintained. Date of most recent determination

K 9 1.5.3 Sample containers are made of glass or some other inert material. O 9 1.5.4 Diution bottles and tubes are made of borosilicate glass or plastic and closed with nubber stoppers, gor screev eages with notoxic liners. K 9 1.5.5 Graduations are indelibly marked on dilution bottles and tubes or an acceptable alternative method is used to censure appropriate volumes. C 9 1.5.6 Graduations are indelibly marked on dilution bottles and ubes or an acceptable alternative method is used to censure appropriate volumes. K 9 1.5.7 Graduations are indelibly marked on dilution bottles and ubes or an acceptable alternative method is used to deliver 1.01. aliquots; nor, are pipets larger than 1.1ml. used to deliver 0.1 mL aliquots; nor, are pipets larger than 1.1ml. used to deliver 0.1 mL aliquots. K 9 1.5.8 In washing reusable pipettes, a succession of at least three fresh water rinses plus a final rinse of distilled/deionized water is used to thoroughly rinse of serial alter detergent. C 11 1.5.10 Kith each load of labware/glassware washed the contact surface of several dry pieces from each load are tested for residual detergent (acid or alkali) with aqueous 0.04% bornouthymol blue. Results are recorded and records are maintained. C 11.6 1.6.1 Autoclave (s) are of sufficient size to accommodate the workload. O 8 1.6.1 Autoc					ingredients and samples.
0 9 I.5.4 Dilution bottles and rubes are made of borosilicate glass or plastic and closed with rubber stoppers, caps or screw caps with nontoxic liners. K 9 I.5.5 Graduations are indebily marked on dilution bottles and ubes or an acceptable alternative method is used to ensure appropriate volumes. C 9 I.5.6 Pipettes used to inoculate the sample deliver accurate aliquots, have unbroken tips and are appropriately graduated. Pipettes larger than 10 mL are not used to deliver ImL aliquots: nor, are pipets larger than 11 mL used to deliver ImL aliquots: nor, are pipets larger than 11 mL used to deliver piettes. a succession of at least three fresh water rinses plus a final rinse of distilled/deionized water is used to thoroughly rinse off all the detergent. C 2 I.5.9 An alkaline or acidic detergent is used for washing glassware/labware. C 11 I.5.10 With each load of labware/glassware washed the contact surface of several dry pieces from each load are tested for residual detergent (acid or alkali) with aqueous 0.04% bromothymol blue. Results are recorded and records maintained. C 11.30 I.6.3 The autoclave maintaineance is performed and the rescords are maintained. C 11,30 I.6.3 The autoclave standards thermometer has been calibrated by a qualified calibration laboratory: or, is checked in-house at the steam point (100°C) if it has been previously calibrated aboth 100°C and calibrated nationing are indexide and point (100°C) if it has been previously calibrated aboth 100°C and 1	K	9		1.5.3	
K 9 1.5.5 Graduations are indelibly marked on dilution bottles and tubes or an acceptable alternative method is used to ensure appropriate volumes. C 9 1.5.6 Pipettes used to inoculate the sample deliver accurate aliquots, have unbroken tips and are appropriately graduated. Pipettes larger than 10 mL used to deliver 0.1 mL aliquots. K 9 1.5.7 Reusable sample containers are capable of being properly washed and sterilized. K 9 1.5.8 In washing reusable pipetes, a succession of at least three fresh water rinses plus a final rinse of distilled/decinized water is used to thoroughly rinse off all the detergent. C 2 1.5.9 An alkaline or acidic detergent is used for washing glassware/labware. C 11 1.5.10 With each load of labware/glassware washed the contact surface of several dry pieces from ceal-load are tested for residual detergent (acid or alkali) with aqueous 0.04% bromothymol blue. Results are recorded and records amaintained. I.6 Sterilization and Decontamination I.6.2 Routine autoclave maintenance is performed and the records are maintained. C 11,30 I.6.3 The autoclave smaintenance is performed and the records are maintained. K 9 I.6.4 An autoclave standards thermometer has been calibrated by analified. K 11 I.6.4 An autoclave standards t	0	9		1.5.4	Dilution bottles and tubes are made of borosilicate glass or plastic and closed
C 9 I.5.6 Pipettes used to inoculate the sample deliver accurate alignets have unbroken tips and are appropriately graduated. Pipettes larger than 1.1mL used to deliver 0.1 mL aliquots. K 9 I.5.7 Reusable sample containers are capable of being properly washed and sterilized. K 9 I.5.7 Reusable sample containers are capable of being properly washed and sterilized. K 9 I.5.8 In washing reusable pipettes, a succession of at least three fresh water rinkes plus a final rinke of distilled/deionized water is used to thoroughly rinke off all the detergent. C 11 I.5.10 With each load of hobware/glassware washed the contact surface of several dry pieces from each load are tested for residual detergent (acid or alkali) with aqueous 0.04% bromothymol blue. Results are recorded and records maintained. C 11.6.1 Autoclave(s) are of sufficient size to accommodate the workload. O 8 I.6.2 Routine autoclave maintenance is performed and the records are maintained. C 11, 30 I.6.3 The autoclave provides a sterilizing temperature of 121±2/C a determined for each load using a calibrated maximum registering device is used in place of the maximum registering thermometer when these are unavailable due to the ban on mercury. K 11 I.6.4 An autoclave standards thermometer has been calibrated by aqualified calibration laboratory; ori, is also recommended but not	K	9		1.5.5	Graduations are indelibly marked on dilution bottles and tubes or an acceptable
K 9 1.5.8 In washing reusable pipettes, a succession of at least three fresh water rinses plus a final rinse of distilled/deionized water is used to thoroughly rinse off all the detergent. C 2 1.5.9 An alkaline or acidic detergent is used for washing glassware/labware. C 11 1.5.10 With each load of labware/glassware washed the contact surface of several dry picces from each load arc tested for residual detergent (acid or alkalis) with aqueous 0.04% bromothymol blue. Results are recorded and records maintained. C 11 1.6.1 Autoclave(s) are of sufficient size to accommodate the workload. O 8 1.6.2 Routine autoclave maintenance is performed and the records are maintained. C 11, 30 1.6.3 The autoclave maintenance is performed and the records are maintained. C 11, 30 1.6.4 Autoclave clave provides a sterilizing temperature of 121±2°C as determined for each load using a calibrated maximum registering thermometer. As an alternative, an appropriate temperature monitoring device is used in place of the maximum registering thermometer has been calibrated by a qualified calibration laboratory. K 11 1.6.5 The autoclave standards thermometer is checked every five (5) years for accuracy at 121°C by a qualified calibration laboratory. K 16 1.6.6 Working autoclave thermometers are checked against the autoclave standards thermometer a	С	9		1.5.6	Pipettes used to inoculate the sample deliver accurate aliquots, have unbroken tips and are appropriately graduated. Pipettes larger than 10 mL are not used to deliver 1mL aliquots; nor, are pipets larger than 1.1mL
K 11 1.6.7 An alkaline or acidic detergent is used to thoroughly rinse off all the detergent. C 2 1.5.9 An alkaline or acidic detergent is used for washing glassware/labware. C 11 1.5.10 With each load of labware/glassware washed the contact surface of several dry pieces from each load are tested for residual detergent (acid or alkali) with aqueous 0.04% bromothymol blue. Results are recorded and records maintained. I.6. Sterilization and Decontamination K 9 1.6.1 Autoclave(s) are of sufficient size to accommodate the workload. O 8 1.6.2 Routine autoclave maintenance is performed and the records are maintained. C 11, 30 1.6.3 The autoclave provides a sterilizing temperature of 121± 2°C as determined for each load using a calibrated maximum registering thermometer. As an alternative, an appropriate temperature monitoring device is used in place of the maximum registering thermometer has been calibrated by a qualified calibration laboratory using a primary standard traceable to NIST or an equivalent authority at 121°C. Calibration at 100°C, the steam point, is also recommended but not required. K 16 1.6.5 The autoclave standards thermometer is checked every five (5) years for accuracy at 121°C by a qualified calibration laboratory; or, is checked in-house at the steam point (100°C) if it has been previously calibrated at both 100°C and 121°C. Any change in temperature at the steam point changes the calibrated temperature at 121°C by the same ma	K	9		1.5.7	Reusable sample containers are capable of being properly washed and sterilized.
C 11 1.5.10 With each load of labware/glassware washed the contact surface of several dry pieces from each load are tested for residual detergent (acid or alkali) with aqueous 0.04% bromothymol blue. Results are recorded and records maintained. K 9 1.6.1 Autoclave(s) are of sufficient size to accommodate the workload. O 8 1.6.2 Routine autoclave maintenance is performed and the records are maintained. C 11, 30 1.6.3 The autoclave provides a sterilizing temperature of 121± 2°C as determined for each load using a calibrated maximum registering thermometer. As an alternative, an appropriate temperature monitoring device is used in place of the maximum registering thermometer when these are unavailable due to the ban on mercury. K 11 1.6.4 An autoclave standards thermometer has been calibrated by a qualified calibration laboratory using a primary standard traceable to NIST or an equivalent authority at 121°C. Calibration at 100°C, the steam point, is also recommended but not required. K 16 1.6.5 The autoclave standards thermometer is checked every five (5) years for accuracy at 121°C by a qualified calibration laboratory; or, is checked in-house at the steam point (hore) risk steam point (10°C) if it has been previously calibrated at both 10°C and 12°C. Any change in temperature at the steam point changes the calibrated temperature at the steam point changes the calibrated temperature at the steam point changes the calibrated temperature at the steam point changes of the training. K 11 1.6.	K	9		1.5.8	a final rinse of distilled/deionized water is used to thoroughly rinse off all the
K 1 1.6.7 graph of the second s	С	2		1.5.9	An alkaline or acidic detergent is used for washing glassware/labware.
K 9 1.6.1 Autoclave(s) are of sufficient size to accommodate the workload. O 8 1.6.2 Routine autoclave maintenance is performed and the records are maintained. C 11, 30 1.6.3 The autoclave provides a sterilizing temperature of 121± 2°C as determined for each load using a calibrated maximum registering thermometer. As an alternative, an appropriate temperature monitoring device is used in place of the maximum registering thermometer has been calibrated by a qualified calibration laboratory using a primary standard traceable to NIST or an equivalent authority at 121°C. Calibration at 100°C, the steam point, is also recommended but not required. K 16 1.6.5 The autoclave standards thermometer is checked every five (5) years for accuracy at 121°C by a qualified calibration laboratory; or, is checked in-house at the steam point (100°C) if it has been previously calibrated at both 100°C and 121°C. Any change in temperature at the steam point changes the calibrated temperature at 121°C by the same magnitude. K 1 1.6.6 Working autoclave thermometers are checked against the autoclave standards thermometer at 121°C yearly. K 11 1.6.7 Spore strips/suspensions appropriate for use in an autoclave media cycle are used monthly according to manufacturer's instructions to evaluate the effectiveness of the sterilization process. Results are recorded and the records maintained. K 11 1.6.8 Heat sensitive tape is used with each autoclave batch. 4. 4. <t< td=""><td>С</td><td>11</td><td></td><td>1.5.10</td><td>dry pieces from each load are tested for residual detergent (acid or alkali) with aqueous 0.04% bromothymol blue. Results are recorded and records</td></t<>	С	11		1.5.10	dry pieces from each load are tested for residual detergent (acid or alkali) with aqueous 0.04% bromothymol blue. Results are recorded and records
0 8 1.6.2 Routine autoclave maintenance is performed and the records are maintained. C 11, 30 1.6.3 The autoclave provides a sterilizing temperature of 121± 2°C as determined for each load using a calibrated maximum registering thermometer. As an alternative, an appropriate temperature monitoring device is used in place of the maximum registering thermometer when these are unavailable due to the ban on mercury. K 11 1.6.4 An autoclave standards thermometer has been calibrated by a qualified calibration laboratory using a primary standard traceable to NIST or an equivalent authority at 121°C. Calibration at 100°C, the steam point, is also recommended but not required. K 16 1.6.5 The autoclave standards thermometer is checked every five (5) years for accuracy at 121°C by a qualified calibration laboratory; or, is checked in-house at the steam point (100°C) if it has been previously calibrated at both 100°C and 121°C. Any change in temperature at the steam point changes the calibrated temperature at 121°C by the same magnitude. M 1 1.6.6 Working autoclave thermometers are checked against the autoclave standards thermometer at 121°C yearly. K 11 1.6.7 Spore strips/suspensions appropriate for use in an autoclave media cycle are used monthly according to manufacturer's instructions to evaluate the effectiveness of the sterilization process. Results are recorded and the records maintained. O 11 1.6.8 Heat sensitive tape is used with each autoclave batch.			1.6 St	erilizati	
C 11, 30 Image: Section 2010 and	K	9		1.6.1	Autoclave(s) are of sufficient size to accommodate the workload.
K 11 I.6.6 For each load using a calibrated maximum registering thermometer. As an alternative, an appropriate temperature monitoring device is used in place of the ban on mercury. K 11 I.6.4 An autoclave standards thermometer has been calibrated by a qualified calibration laboratory using a primary standard traceable to NIST or an equivalent authority at 121°C. Calibration at 100°C, the steam point, is also recommended but not required. K 16 I.6.5 The autoclave standards thermometer is checked every five (5) years for accuracy at 121°C by a qualified calibration laboratory; or, is checked in-house at the steam point (100°C) if it has been previously calibrated at both 100°C and 121°C. Any change in temperature at the steam point changes the calibrated temperature at 121°C by the same magnitude. K 1 I.6.6 Working autoclave thermometers are checked against the autoclave standards thermometer at 121°C yearly. Date of most recent determination	0	8		1.6.2	Routine autoclave maintenance is performed and the records are maintained.
K 16 I.6.5 The autoclave standards thermometer is checked every five (5) years for accuracy at 121°C by a qualified calibration laboratory; or, is checked in house at the steam point (100°C) if it has been previously calibrated at both 100°C and 121°C. Any change in temperature at the steam point changes the calibrated temperature at 121°C by the same magnitude. K 1 I.6.6 Working autoclave thermometers are checked against the autoclave standards thermometers are checked against the autoclave standards thermometers are checked against the autoclave standards thermometer at 121°C by the same magnitude. K 1 I.6.6 Working autoclave thermometers are checked against the autoclave standards thermometer at 121°C yearly. K 11 I.6.7 Spore strips/suspensions appropriate for use in an autoclave media cycle are used monthly according to manufacturer's instructions to evaluate the effectiveness of the sterilization process. Results are recorded and the records maintained. O 11 I.6.8 Heat sensitive tape is used with each autoclave batch. K 11, 13 I.6.9 Autoclave sterilization records including length of sterilization, total heat exposure time and chamber temperature are maintained. Type of record: Autoclave log, computer printout or chart recorder tracings. (<i>Circle appropriate type or types.</i>) K 11 I.6.10 For dry heat sterilized material, the hot-air sterilizing oven provides heating and	С	11, 30		1.6.3	for each load using a calibrated maximum registering thermometer. As an alternative, an appropriate temperature monitoring device is used in place of the maximum registering thermometer when these are unavailable due
K 16 I.6.5 The autoclave standards thermometer is checked every five (5) years for accuracy at 121°C by a qualified calibration laboratory; or, is checked in-house at the steam point (100°C) if it has been previously calibrated at both 100°C and 121°C. Any change in temperature at the steam point changes the calibrated temperature at 121°C by the same magnitude. K 1 Image: Imag	K	11		1.6.4	calibration laboratory using a primary standard traceable to NIST or an equivalent authority at 121°C. Calibration at 100°C, the steam point, is also
K 1 Image: Interpret type of record: Autoclave sterilized material, the hot-air sterilizing oven provides heating and K 11 Image: Interpret type of types.)	K	16		1.6.5	The autoclave standards thermometer is checked every five (5) years for accuracy at 121°C by a qualified calibration laboratory; or, is checked in-house at the steam point (100°C) if it has been previously calibrated at both 100°C and 121°C. Any change in temperature at the steam point changes the calibrated
K 11 I.6.7 Spore strips/suspensions appropriate for use in an autoclave media cycle are used monthly according to manufacturer's instructions to evaluate the effectiveness of the sterilization process. Results are recorded and the records maintained. O 11 I.6.8 Heat sensitive tape is used with each autoclave batch. K 11, 13 I.6.9 Autoclave sterilization records including length of sterilization, total heat exposure time and chamber temperature are maintained. K 11 I.6.9 For dry heat sterilized material, the hot-air sterilizing oven provides heating and					Date of most recent determination
K11I.6.7Spore strips/suspensions appropriate for use in an autoclave media cycle are used monthly according to manufacturer's instructions to evaluate the effectiveness of the sterilization process. Results are recorded and the records maintained.O11I.6.8Heat sensitive tape is used with each autoclave batch.K11, 13I.6.9Autoclave sterilization records including length of sterilization, total heat exposure time and chamber temperature are maintained.K11I.6.10For dry heat sterilized material, the hot-air sterilizing oven provides heating and	K	1		1.6.6	
O111.6.8Heat sensitive tape is used with each autoclave batch.K11, 131.6.9Autoclave sterilization records including length of sterilization, total heat exposure time and chamber temperature are maintained.K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K111.6.10K11					
K 11, 13 Image: Autoclave sterilization records including length of sterilization, total heat exposure time and chamber temperature are maintained. Type of record: Autoclave log, computer printout or chart recorder tracings. (Circle appropriate type or types.) K 11 Image: Autoclave sterilized material, the hot-air sterilizing oven provides heating and	K	11		1.6.7	used monthly according to manufacturer's instructions to evaluate the effectiveness of the sterilization process. Results are recorded and the records
K11I.6.10For dry heat sterilized material, the hot-air sterilizing oven provides heating and	0	11		1.6.8	Heat sensitive tape is used with each autoclave batch.
K 11 1.6.10 For dry heat sterilized material, the hot-air sterilizing oven provides heating and	К	11, 13		1.6.9	exposure time and chamber temperature are maintained. Type of record: Autoclave log, computer printout or chart recorder tracings.
	K	11		1.6.10	For dry heat sterilized material, the hot-air sterilizing oven provides heating and

K	9		1.6.11	A thermometer capable of determining temperatures accurately in the range of 160 to 180°C is used to monitor the operation of the hot-air sterilizing oven
K	13		1.6.12	Records of temperatures and exposure times are maintained for the operation of the hot-air sterilizing oven during use.
K	11		1.6.13	Spore strips/suspensions are used quarterly to evaluate the effectiveness of the sterilization process in the hot-air oven. Records are maintained.
K	11		1.6.14	Reusable sample containers are sterilized for 60 minutes at 170°C in a hot-air oven or autoclaved for 15 minutes at 121°C.
С	1		1.6.15	The sterility of reusable sample containers is determined for each load
				sterilized. The results are recorded and the records maintained.
С	1		1.6.16	The sterility of pre-sterilized disposable sample containers is determined for
V	0		1 (17	each lot received. Results are recorded and the records maintained.
K	9		1.6.17	Reusable pipettes are stored and sterilized in aluminum or stainless steel canisters.
K	9		1.6.18	Reusable pipettes (in canisters) are sterilized in a hot-air oven at 170°C for 2 hours.
C	2		1.6.19	The sterility of reusable pipettes is determined with each load sterilized. Results are recorded and records maintained.
С	2		1.6.20	The sterility of pre-sterilized disposable pipettes is determined with each lot
C			1.0.20	received. Results are recorded and the records maintained.
K	18		1.6.21	Hardwood applicator transfer sticks are properly sterilized.
				Method of sterilization
С	2		1.6.22	The sterility of the hardwood applicator transfer sticks is checked routinely. Results are recorded and the records maintained.
0	13		1.6.23	Spent broth cultures and agar plates are decontaminated by autoclaving for at
				least 30 minutes before conventional disposal.
				paration
K	3, 5		1.7.1	Media is commercially dehydrated except in the case of medium A-1 which
				must be prepared from the individual components and modified MacConkey agar which may be prepared from its components.
K	11		1.7.2	Media is prepared according to manufacturer's instructions.
0	11		1.7.3	Dehydrated media and media components are properly stored in a cool, clean,
Ŭ			1.7.5	dry place.
0	11		1.7.4	Dehydrated media are labeled with date of receipt and date opened.
С	12		1.7.5	Caked or expired media or media components are discarded.
С	11		1.7.6	Reagent water is distilled or deionized (circle appropriate choice), tested monthly and exceeds 0.5 megohm-cm resistance (2 megohms-cm in-line) or is less than 2.0 µSiemens/cm conductivity at 25°C. (<i>Circle the appropriate</i> <i>water quality descriptor determined.</i>) Results are recorded and the records maintained.
С	11		1.7.7	Reagent water is analyzed for residual chlorine monthly and is at a non- detectable level (< 0.1 mg/L). Results are recorded and the records maintained.
		1		Snacity method at deterministion
V	11		170	Specify method of determination
K	11		1.7.8	Reagent water contains <100 CFU/mL as determined monthly using the heterotrophic plate count method. Results are recorded and the records
				Reagent water contains <100 CFU/mL as determined monthly using the heterotrophic plate count method. Results are recorded and the records maintained.
K K K	11 11 9		1.7.8 1.7.9 1.7.10	Reagent water contains <100 CFU/mL as determined monthly using the heterotrophic plate count method. Results are recorded and the records

1		_	1	
C	11		1.7.11	Total time of exposure of sugar broths to autoclave temperatures does not exceed 45 minutes.
С	1		1.7.12	Media sterility is determined for each load sterilized. Results are recorded and the records maintained.
С	1		1.7.13	Media productivity is determined using media-appropriate, properly diluted positive and negative control cultures for each lot of dehydrated media received or with each batch of media prepared when the medium is made from its individual components.
0	9		1.7.14	Sterile phosphate buffered dilution water is used as the sample diluent.
K	11		1.7.15	The pH of the prepared media is determined after sterilization to ensure that it is consistent with manufacturer's requirements. Results are recorded and records are maintained.
		1.8 Sto	rage of	Prepared Culture Media
K	9		1.8.1	Prepared culture media are stored in a cool, clean, dry space where excessive evaporation and the danger of contamination are minimized.
K	5,11		1.8.2	Brilliant green bile 2% broth and A-1 media are stored in the dark.
K	13		1.8.3	Stored media are labeled with the storage expiration date or the sterilization date.
K	9		1.8.4	Storage of prepared culture media at room temperature does not exceed 7 days.
K	2		1.8.5	Storage under refrigeration of prepared culture media with loose fitting closures shall not exceed 1 month.
K	11		1.8.6	Storage under refrigeration of prepared culture media with screw-cap closures does not exceed 3 months.
K	17		1.8.7	All prepared MPN broth media stored under refrigeration must reach room temperature prior to use. Culture tubes containing any type of precipitate or Durham tubes containing air bubbles are discarded.
	1	1	P	PART II - SEAWATER SAMPLES
		2.1 Co		and Transportation of Samples
С	11		2.1.1	Sample containers are of a suitable size to contain at least 110 mL of sample
				and to allow adequate headspace for proper shaking. Seawater samples are
				collected in clean, sterile, watertight, properly labeled sample containers.
K	1		2.1.2	Samples are identified with collectors name, harvest area, sampling station, time and date of collection.
С	9		2.1.3	Immediately after collection, seawater samples are placed in dry storage (ice chest or equivalent) capable of maintaining a temperature of 0 to 10°C with ice or cold packs for transport to the laboratory. Once received, the samples are placed in the refrigerator unless processed immediately.
0	1		2.1.4	A temperature blank is used to represent the temperature of samples upon receipt at the laboratory. Temperature should be equivalent or less than that of
				the growing area waters. Results are recorded and maintained.
С	9		2.1.5	Analysis of the sample is initiated as soon as possible after collection. Seawater samples are not tested if they have been held for more than 30
<u> </u>			<u> </u> 2 2 1	hours from the time of collection. Bacteriological Examination of Seawater by the APHA MPN
C	9		2.2.1	Lactose broth or lauryl tryptose broth is used as the presumptive medium.
				(Circle appropriate one.)
C	2		2.2.2	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained.
				Positive productivity control Negative productivity control
С	9		2.2.3	Sample and dilutions of sample are shaken vigorously (25 times in a 12" arc in 7 seconds) before inoculation.
С	9		2.2.4	In a multiple dilution series not less than 3 tubes per dilution are used (5

				tubes are recommended).
С	6		2.2.5	In a single dilution series not less than 12 tubes are used (for depuration at
				least 5 tubes are used).
C	6		2.2.6	In a single dilution series, the volumes analyzed are adequate to meet the needs of routine monitoring.
				Sample volume inoculated
				Range of MPN
				Strength of media used
K	9		2.2.7	Inoculated tubes are incubated in air at 35 ± 0.5 °C.
С	2		2.2.8	Appropriately diluted process control cultures accompany the samples <i>throughout both the presumptive and confirmed phases of incubation</i> . Results are recorded and the records maintained.
				Positive process control Negative process control
K	9		2.2.9	Inoculated tubes are read after 24 ± 2 hours and 48 ± 3 hours of incubation and transferred at both time interval if positive for growth (the presence of turbidity) and gas or effervescence in the culture tube. These tubes are considered
				presumptive positive requiring further confirmatory testing.
				2.3 Confirmed Test for Seawater by APHA MPN
С	9		2.3.1	Brilliant green bile 2% broth (BGB) is used as the confirmatory medium for total coliforms.
С	9		2.3.2	EC medium is used as the confirmatory medium for fecal coliforms.
C	2		2.3.3	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained.
				Positive productivity controlNegative productivity control
K	9, 11		2.3.4	Transfers are made to BGB/EC by either sterile loop or sterile hardwood transfer stick from positive presumptive tubes incubated for 24 and 48 hours as appropriate. (<i>Circle the method of transfer.</i>)
С	9		2.3.5	BGB tubes are incubated at $35 \pm 0.5^{\circ}$ C.
K	9		2.3.6	BGB tubes are read after 48 ± 3 hours of incubation.
С	9		2.3.7	EC tubes are incubated in a circulating waterbath maintained at $44.5 \pm 0.2^{\circ}$ C.
С	9		2.3.8	EC tubes are read after 24 ± 2 hours of incubation.
С	9		2.3.9	The presence of turbidity and any amount of gas or effervescence in the
	<u> </u>			culture tube constitutes a positive test.
17		2.4 Co		ion of Results – APHA MPN
K	9		2.4.1	Results of multiple dilution tests are read from tables in <i>Recommended</i> <i>Procedures for the Examination of Sea Water and Shellfish</i> , Fourth Edition.
K	7		2.4.2	Results from single dilution series are calculated from Hoskins' equation or interpolated from Figure 1, Public Health Report 1621 entitled "Most Probable Numbers for Evaluation of Coli aerogenes Tests by Fermentation Tube Method".
С	7,9		2.4.3	Results are reported as MPN/100 mL of sample.
			2.5 I	Bacteriological Examination of Seawater by the MA-1 Method
С	5		2.5.1	A-1 medium complete is used in the analysis.
С	2,31		2.5.2	A-1 medium without salicin is used in the analysis. Comparability testing

				supports use of A-1 medium without salicin. Study records are available.
С	5		2.5.3	A-1 medium sterilized for 10 minutes at 121°C.
С	2		2.5.4	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained.
С	9		2.5.5	Positive productivity controlNegative productivity control Sample and dilutions of sample are shaken vigorously (25 times in a 12" are in 7 seconds) before inoculation.
С	9		2.5.6	In a multiple dilution series not less than 3 tubes per dilution are used (5 tubes are recommended).
С	6		2.5.7	In a single dilution series at least 12 tubes are used.
С	6		2.5.8	In a single dilution series, the volumes analyzed are adequate to meet the needs of routine monitoring. Sample volume inoculated Range of MPN Strength of media used
С	2		2.5.9	Appropriately diluted process control cultures accompany the samples throughout both resuscitation and waterbath incubation Results are recorded and the records maintained. Positive process control Negative process control
С	2,5		2.5.10	Inoculated tubes are placed in an air incubator at 35 ± 0.5 °C for 3 ± 0.5 hours of resuscitation.
С	5		2.5.11	After 3 ± 0.5 hours resuscitation at 35°C, inoculated tubes are incubated at 44.5 ± 0.2 °C in a circulating waterbath for the remainder of the 24 ± 2 hours.
С	5		2.5.12	The presence of turbidity and any amount of gas or effervescence in the culture tube constitutes a positive test.
		2.6 Co	mputat	ion of Results – APHA MPN
K	9		2.6.1	Results of multiple dilution tests are read from tables in <i>Recommended</i> <i>Procedures for the Examination of Sea Water and Shellfish</i> , 4 th Edition.
K	7		2.6.2	Results from single dilution series are calculated from Hoskins' equation or interpolated from Figure 1, Public Health Report 1621 entitled "Most Probable Numbers for Evaluation of Coli aerogenes Tests by Fermentation Tube Method".
С	7,9		2.6.3	Results are reported as MPN/100 mL of sample.
				ogical Analysis of Seawater by Membrane Filtration (MF) using gar - Materials and Equipment
С	23, 24		2.7.1	When used for elevated temperature incubation in conjunction with ethafoam resuscitation, the temperature of the hot air incubator is maintained at $44.5 \pm 0.5^{\circ}$ C under any loading capacity.
С	23		2.7.2	When using a waterbath for elevated temperature incubation, the level of the water completely covers the plates.
С	23		2.7.3	Pre-sterilized plastic or sterile glass culture plates that are clear, flat bottomed, free of bubbles and scratches with tight fitting lids are used.
С	2		2.7.4	The sterility of pre-sterilized culture plates is determined for each lot received. Results are recorded and the records maintained.
Κ	11		2.7.5	Colonies are counted with the aid of magnification.
С	11, 23		2.7.6	Membrane filters are made from cellulose ester material, white, grid marked, 47 mm in diameter with a pore size of 0.45 μm and certified by the manufacturer for fecal coliform analyses.
С	2		2.7.7	Lot number, date of receipt and if provided the expiration date of the membrane filters are recorded and records maintained.

С	2		2.7.8	When initiating monitoring by mTEC or switching brands or types of membrane filters used and no previous lots of filters are available for comparing acceptable performance, an appropriate method for determining the suitability of the lot is developed and the comparison testing implemented. The results are recorded and this record is maintained.
K	2, 11		2.7.9	New lots of membrane filters are checked by comparing recovery of fecal
C	2		2 7 10	coliform organisms against membrane filters from previously acceptable lots.
С	2		2.7.10	The sterility of each lot or autoclave batch of membrane filters are checked before use.
K	2		2.7.11	Membrane filters which are beyond their expiration date are not used.
0	11		2.7.12	Forceps tips are clean.
0	11		2.7.13	Forceps tips are smooth without pitting or corrugations to damage the filters
K	11		2.7.14	being manipulated. Forceps are dipped in alcohol and flame sterilized between sample filters.
		_ H		
К	11		2.7.15	If indelible graduation marks are used on clear glass or plastic funnels to measure sample volumes, their accuracy is checked gravimetrically or with a Class A graduated cylinder before use and periodically rechecked. Funnels having a tolerance greater than 2.5% are not used. Checks are recorded and records maintained.
K	11		2.7.16	Membrane filtration units are made of stainless steel, glass or autoclavable plastic free of scratches, corrosion and leaks.
C	11		2.7.17	Membrane filter assemblies are autoclave sterilized for 15 minutes at 121°C
Ŭ		•••		prior to the start of a filtration series.
0	11, 23, 26		2.7.18	A UV sterilization unit is used to disinfect filter assemblies between sample and filtration runs.
K	11		2.7.19	The effectiveness of the UV sterilization unit is determined by biological testing monthly. Results are recorded and records maintained.
K	2		2.7.20	Maintenance of the UV sterilization unit is performed as needed. This maintenance is documented and the records maintained.
		2.8 Me	dia Pre	paration and Storage – MF using mTEC Agar
K	11		2.8.1	Phosphate buffered saline is used as the sample diluent and filter funnel rinse.
C	11	H	2.8.2	The phosphate buffered saline is properly sterilized.
K	23	H	2.8.3	A sufficient amount of medium (4-5 mL) is used in each plate.
0	11	Ħ	2.8.4	Refrigerated prepared plates are stored for no more than 2 weeks in sealed plastic bags or containers to minimize evaporation.
1		2.9 Sa	mple Ar	alyses - MF using mTEC Agar
С	24		2.9.1	mTEC agar is used.
C	2	đ	2.9.2	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained. Positive productivity control Negative productivity control
C	23		2.9.3	The sample is shaken vigorously (25 times in a 12" arc in 7 seconds) before
				filtration.
C	23		2.9.4	The membrane is placed grid side up within the sterile filter apparatus.
С	23, 25		2.9.5	Sample volumes tested are consistent with the sampling regime employed (i.e., half log or other appropriate dilutions are used with systematic random sampling).
С	23		2.9.6	Sample volumes are filtered under vacuum.
K	26		2.9.7	The pressure of the vacuum pump does not exceed 15 psi.
С	23, 26		2.9.8	The sides of the filter funnel are rinsed at least twice with 20-30 mL of

				sterile phosphate buffered saline after sample filtration.
С	23		2.9.9	The membrane filter is removed from the filtering apparatus with sterile
C	25		2.9.9	forceps and rolled onto mTEC agar so that no bubbles form between the
				filter and the agar.
С	11		2.9.10	Blanks are run at the beginning of filtration, after every 10 th aliquot and at
				the end of the filtration run to check the sterility of the testing system
				(phosphate buffered saline, filter funnel, forceps, membrane filter, media and culture plate).
С	2,11		2.9.11	Appropriately diluted process control cultures accompany the samples
				throughout both resuscitation and elevated temperature incubation.
				Results are recorded and the records maintained.
				Positiva process control Nagativa process control
C	11, 23, 24		2.9.12	Positive process control Negative process control Inoculated plates are placed inverted into a watertight, tightly sealed
C	11, 25, 24		2,7,12	container prior to being placed in the air incubator and incubated at 35 +
				0.5°C for 2 hours of resuscitation. Alternatively inoculated plates may be
				placed in ethafoam prior to air incubation at $44.5 \pm 0.5^{\circ}$ C for 24 ± 2 hours.
C	11, 23, 24		2.9.13	After 2 hours of resuscitation at 35°C, the watertight, tightly sealed
				containers are transferred to a circulating waterbath at 44.5 + 0.2°C, submerged completely and incubated for 22-24 hours.
				2.10 Computation of Results - MF using mTEC Agar
С	23		2.10.1	All yellow, yellow-green or yellow-brown colonies are counted.
C	23	Ħ	2.10.2	Only plates having 80 or fewer colonies are counted. If it is unavoidable to
				use plates having more than 80 colonies, counts are given as >80 x 100/the
				volume of sample filtered.
C	2, 11, 23		2.10.3	When multiple dilutions are filtered, the laboratory has developed a
				procedure for assessing the contribution of all positive dilutions to the final count.
С	23, 11		2.10.4	The number of fecal coliforms is calculated by the following equation:
	,			v oı
				Number of fecal coliforms per 100 mL = [number of colonies counted per
~				plate used in the count / volume (s) of sample filtered in ml] x 100.
C	23, 11			Results are reported as CFU/100 mL of sample.
				ART III - SHELLFISH SAMPLES
				and Transportation of Samples
C	9			A representative sample of shellstock is collected.
K	9		3.1.2	Shellstock samples are collected in clean, waterproof, puncture resistant containers loosely sealed.
K	9		3.1.3	Shellstock samples are labeled with collector's name, type of shellstock, the
				source or harvest area, sampling station, time, date and place (if applicable) of
				collection.
С	9		3.1.4	Immediately after collection, shellfish samples are placed in dry storage (ice
				chest or equivalent) which is maintained between 0 and 10°C with ice or
				cold packs for transport to the laboratory. Once received, the samples are placed under refrigeration unless processed immediately.
С	1		3.1.5	Analysis of the samples is initiated as soon as possible after collection.
	_			Shellfish samples are not tested if the time interval between collection and
				analysis exceeds 24 hours.
		3.2 Pr		on of Shellfish for Examination
K	2,11		3.2.1	Shucking knives, scrub brushes and blender jars are (autoclave) sterilized for 15
0	2		3.2.2	minutes prior to use. Blades of shucking knives are not corroded.
0	<u> </u>		5.2.2	Diades of Shucking Knives are not confound.

0	9		3.2.3	The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris.
0	2		3.2.4	The faucet used for rinsing the shellstock does not contain an aerator.
K	9	H	3.2.5	Shellstock are scrubbed with a stiff, sterile brush and rinsed under tap water of
			5.2.5	drinking water quality.
0	9		3.2.6	Shellstock are allowed to drain in a clean container or on clean towels prior to
		· •		opening.
K	9		3.2.7	Immediately prior to shucking, the hands (or gloved hands) of the analyst are
				thoroughly washed with soap and water and rinsed in 70% alcohol.
C	9		3.2.8	Shellstock are not shucked directly through the hinge.
С	9		3.2.9	Contents of shellstock (liquor and meat) are shucked into a sterile, tared
TZ			2.2.10	blender jar or other sterile container.
K	9		3.2.10	At least 200 grams of shellfish meat or a quantity of meat sufficient to cover the blender blades is used for the analysis.
K	9		3.2.11	A representative sample of at least 12 shellfish is used for the analysis.
K	2	╞┝╋╴	3.2.12	The sample is weighed to the nearest 0.1 gram and an equal amount by weight of
			5.2.12	diluent is added.
0	9		3.2.13	Sterile phosphate buffered dilution water is used as the sample diluent.
C	9		3.2.14	Samples are blended at high speed for 60 to 120 seconds until homogenous.
K	9		3.2.15	APHA Recommended Procedures for the Examination of Sea Water And
				Shellfish, Fourth Edition is followed for the analysis of previously shucked and
				frozen shellfish meats.
				ysis for Fecal Coliform Organisms, Presumptive Test, APHA
С	9		3.3.1	Appropriate strength lactose or lauryl tryptose broth is used as presumptive media in the analysis. (Circle the medium used.)
С	2		3.3.2	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained. Positive productivity control Negative productivity control
K	9		3.3.3	Immediately (within 2 minutes) after blending, the ground sample is diluted and
				inoculated into tubes of presumptive media.
С	9		3.3.4	No fewer than 5 tubes per dilution are used in a multiple dilution MPN
				series.
С	9		3.3.5	Allowing for the initial 1:1 dilution of the sample, appropriate portions are inoculated (i.e., 2 ml of original 1:1 dilution for the 1 g portion) and diluted for subsequent inoculation (i.e., 20 ml of 1:1 diluted sample to 80 ml of diluent or the equivalent for 0.1 g portion). All successive dilutions are prepared conventionally.
K	6		3.3.6	In a single dilution series, the volumes examined are adequate to meet the needs
				of routine monitoring.
				Sample volume inoculated Range of MPN
				Strength of media used
С	2		3.3.7	Appropriately diluted process control cultures accompany the samples
			0.0.1	
1	_		0.0.7	throughout both the presumptive and confirmed phases of incubation.
			5.5.7	Results are recorded and the records maintained.
				Results are recorded and the records maintained. Positive Process control Negative Process control
K	9		3.3.8	Results are recorded and the records maintained.Positive Process control Negative Process controlInoculated media are incubated at $35 \pm 0.5^{\circ}$ C.
K K				Results are recorded and the records maintained.Positive Process control Negative Process controlInoculated media are incubated at 35 ± 0.5 °C.Tubes are read after 24 ± 2 hours of incubation and transferred if positive for
	9		3.3.8	Results are recorded and the records maintained.Positive Process control
	9		3.3.8 3.3.9	Results are recorded and the records maintained.Positive Process control Negative Process controlInoculated media are incubated at 35 ± 0.5 °C.Tubes are read after 24 ± 2 hours of incubation and transferred if positive for

С	9		3.4.1	EC medium is used as the confirmatory medium.
С	2		3.4.2	The appropriate positive and negative productivity controls for the presumptive media are used. The results are recorded and the records maintained.
				Positive productivity controlNegative productivity control
K	9, 11		3.4.3	Transfers are made to EC medium by either sterile loop or hardwood sterile transfer sticks from positive presumptives. (<i>Circle the method of transfer.</i>)
С	9		3.4.4	EC tubes are incubated in a circulating waterbath at 44.5 ± 0.2 °C
K	9		3.4.5	EC tubes are read for gas production after 24 ± 2 hours of incubation.
С	9		3.4.6	The presence of turbidity and any amount of gas and/or effervescence in the Durham tube constitutes a positive test.
		3.5 Co	mputati	ion of Results for MPN Analyses
K	9		3.5.1	Results of multiple dilution tests are read from tables in <i>Recommended</i> <i>Procedure for the Examination of Sea Water and Shellfish</i> , 4th Edition and multiplied by the appropriate dilution factor.
К	7		3.5.2	Results from single dilution series are calculated from Hoskins' equation or interpolated from Figure 1, Public Health Report 1621 entitled "Most Probable Numbers for Evaluation of Coli aerogenes Tests by Fermentation Tube Method".
С	9		3.5.3	Results are reported as MPN/100 grams of sample.
		3.6 Sta	ndard]	Plate Count Method
0	20		3.6.1	A standard plate count (SPC) analysis may be performed in conjunction with the analysis for fecal coliform organisms.
К	9		3.6.2	In the standard plate count procedure at least four plates are used, duplicates of two dilutions. One of the dilutions should produce colonies of 30 to 300 per plate.
K	2		3.6.3	Fifteen to 20 mL of tempered sterile plate count agar is used per plate.
С	9		3.6.4	Agar tempering bath maintains the agar at 44-46°C.
С	9		3.6.5	An agar based temperature control having a similar volume and shape as the tempering plate count agar is used in the tempering bath.
K	9		3.6.6	Samples or sample dilutions to be plated are shaken vigorously (25 times in a 12" arc in 7 seconds) before plating.
С	9		3.6.7	Not more than 1 mL nor less than 0.1 mL of sample or sample dilution is plated.
K	11		3.6.8	Control plates are used to check air quality and the sterility of the agar and the diluent.
K	9,21		3.6.9	Solidified plates are incubated at 35 ± 0.5 °C for 48 ± 3 hours inverted and stacked no more than four high.
K	9		3.6.10	Quebec Colony Counter or its equivalent is used to provide the necessary magnification and visibility for counting plates.
K	1		3.6.11	A hand tally or its equivalent is used for accuracy in counting.
		3.7 Co		ion of Results -SPC
K	9		3.7.1	Colony counts determined in accordance with Part III, A, Sections 4.31 through 4.33 in <i>Recommended Procedures for the Examination of Sea Water and Shellfish</i> , Fourth Edition.
С	19		3.7.2	Colony counts are reported as CFU/g of sample.
		3.8 Ba	cteriolo	gical Analysis of Shellfish Using the ETCP
С	2,3		3.8.1	Prepared modified MacConkey agar is used on the day that it is made.
K	3		3.8.2	Double strength modified MacConkey agar is used.
С	3		3.8.3	Prepared double strength modified MacConkey agar is heated to boiling, removed from the heat, and boiled again. This agar is never autoclaved.

		_	2.0.1			
K	2, 3		3.8.4	Twice boiled, double strength modified MacConkey agar and is maintained in a tempering bath at 45 to 50°C until used.		
K	2, 3		3.8.5	Phosphate buffered saline is used as the sample diluent in the ETCP.		
С	2, 3		3.8.6	The phosphate buffered saline is tempered at 45 - 50°C to prevent premature solidification of the agar.		
С	9		3.8.7	The sample homogenate is cultured within 2 minutes of blending.		
С	2,3		3.8.8	Six grams of shellfish (12 grams of homogenate if initially diluted 1:1) is		
				placed into a sterile container and the contents brought up to 60 mL with		
			_	sterile, tempered phosphate buffered saline.		
K	3		3.8.9	Sixty (60) mL of tempered, twice boiled double strength Modified MacConkey		
TZ IZ			2.0.10	Agar is added.		
K	2,3, 22		3.8.10	The container is gently swirled or slowly inverted once to mix the contents,		
C	1		3.8.11	which are subsequently distributed uniformly over six plates.		
C	1		5.0.11	Media and diluent sterility are determined with each use. Results are recorded and the records maintained.		
С	1		3.8.12	Media productivity is determined using media appropriate properly diluted		
				pour plated positive and negative control cultures for each batch of		
				Modified MacConkey agar prepared.		
				Positive control culture Negative control culture		
С	3, 13		3.8.13	When solidified, the plates are placed inverted into an air incubator at $45.5 \pm 0.5^{\circ}$ C for 18 to 30 hours of incubation.		
С	2		3.8.14	Plates are stacked no more than three high in the incubator.		
С	2		3.8.15	Appropriately diluted pour plated process control cultures accompany each		
		—		set of samples throughout incubation. The results are recorded and the		
				records maintained.		
				Positive process control Negative process control		
	3.9 Computation of Results - ETCP					
K	11		3.9.1	Quebec Colony counter or its equivalent is used to provide the necessary		
0	1		3.9.2	magnification and visibility for counting. A hand tally or its equivalent is used to aid in counting.		
C		┝┝┥	3.9.2	All brick red colonies greater than 0.5 mm in diameter are totaled over all		
C	3, 6		5.9.5	0		
С	3		3.9.4	the plates and multiplied by a factor of 16.7.		
L	3			Results are reported as CFU/100 grams of sample.		
			0	l Examination of Soft-shelled Clams and American Oysters for Male		
				hage (MSC)		
17	20	3.10 M		nipment and Supplies		
K	30		3.10.1	Sample containers used for the shucked sample are sterile, made of glass or some other inert material (i.e. polypropylene) and hold $100 - 125$ mL.		
C	27, 28		3.10.2	The refrigerated centrifuge used must have the capacity to accommodate		
				the amount of shellfish sample required for the procedure, perform at 9000		
IZ IZ			2 10 2	x g and maintain a temperature of 4°C.		
K	9		3.10.3	The level of water in the tempering bath covers the level of liquid and agar in the container or culture tubes.		
С	27, 28		3.10.4	Sterile 0.22 µm pore size syringe filters and pre-sterilized plastic or sterile		
				glass syringes are used to sterilize the antibiotic solutions.		
V		-	2 10 5	The sterility of each lot of pre-sterilized syringes and syringe filters is		
K	1		3.10.5	The sternity of each lot of pre-sternized synnges and synnge inters is		
<u>к</u>	1		5.10.5	determined. Results are recorded and records maintained.		
K	1 1		3.10.5	determined. Results are recorded and records maintained. The sterility of each batch of reusable glass syringes is determined. Results are		
К	1		3.10.6	determined. Results are recorded and records maintained. The sterility of each batch of reusable glass syringes is determined. Results are recorded and records maintained.		
				determined. Results are recorded and records maintained. The sterility of each batch of reusable glass syringes is determined. Results are		

С				Sterile disposable 50 mL centrifuge tubes are used and their sterility is determined with each lot. Results are recorded and records maintained.			
	3.11 MSC Media Preparation						
K	28		3.11.1	Media preparation and sterilization is according to the validated method.			
K	27, 28		3.11.2	Bottom agar, double strength soft agar and growth broth are prepared from their individual components.			
K	27, 28		3.11.3	Soft agar is prepared double strength in volumes of 2.5 mL.			
С	27, 28			The streptomycin and ampicillin solutions are added to tempered bottom			
	agar and vortex for 2 minutes on stir plate.						
0	27, 28	┝┝┥	3.11.5	Storage of the bottom agar under refrigeration does not exceed 1 month.			
K	27, 28		3.11.6	Unsterilized soft agar is stored at -20 °C -15C for up to 3 months.			
K				The soft agar is removed from the freezer and sterilized for 15 minutes at 121°C before use.			
K			3.11.8	brage of growth broth in the refrigerator in loosely capped tubes/bottles does t exceed 1 month and in screw capped tubes/bottles does not exceed 3 onths.			
K	27, 28		3.11.9	Bottom agar plates are allowed to reach room temperature before use.			
		3.12 P	reparati	on of the Soft-Shelled Clams and American Oysters for MSC Analysis			
K	2,11		3.12.1	Shucking knives, scrub brushes and blender jars are autoclave sterilized for 15 minutes prior to use.			
0	2		3.12.2	The blades of shucking knives are not corroded.			
0	9 3.12.3 The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris.		The hands of the analyst are thoroughly washed with soap and water immediately prior to cleaning the shells of debris.				
0	2		3.12.4	The faucet used for rinsing the shellfish does not contain an aerator.			
K			The shellfish are scrubbed with a stiff, sterile brush and rinsed under tap water				
				of drinking water quality.			
0	9		3.12.6	The shellfish are allowed to drain in a clean container or on clean towels unlayered prior to shucking.			
K	9			Immediately prior to shucking, the hands (or gloved hands) of the analyst are thoroughly washed with soap and water and rinsed in 70% alcohol.			
С	9		3.12.8	Shellfish are not shucked through the hinge.			
С	9		3.12.9	The contents of shellfish (liquor and meat) are shucked into a sterile, tared blender jar or other sterile container.			
K	9		3.12.10	A representative sample of at least 12 shellfish is used for the analysis.			
K	2, 19		3.12.11	The sample is weighed to the nearest 0.1 gram.			
	3.13 MSC Sample Analysis		mple Analysis				
С	28		3.13.1	E.coli <i>Famp</i> ATCC 700891 is the bacterial host strain used in this procedure.			
K	27, 28		3.13.2	Host cell growth broth is tempered at $36 \pm 1^{\circ}$ C and vortexed (or shaken) to aerate prior to inoculation with host cells.			
K	27, 28		3.13.3	Several host cell colonies are transferred to a tube of tempered, aerated growth broth and incubated at $36 \pm 1^{\circ}$ C for 4-6 hours to provide host cells in log phase			
				growth for sample analysis.			
C	27, 28	╵└	3.13.4	After inoculation, the host cell growth broth culture is not shaken.			
С	28		3.13.5	A 2:1 mixture of sterile growth broth to shellfish tissue is used for eluting the MSC.			
С	28		3.13.6	The elution mixture is prepared w/v by weighing the sample and adding two equal portions of sterile growth broth by volume to the shellfish tissue.			
С	28		3.13.7	The elution mixture is homogenized at high speed for 180 seconds.			
C	28		3.13.8	Immediately after blending, 33 grams of the homogenized elution mixture			

				are weighed into centrifuge tubes.	
С	28		3.13.9	The homogenized elution mixture is centrifuged for 15 minutes at 9000 x g at 4°C.	
С	27, 28		3.13.10	The supernatant is pipetted off, weighed and the weight recorded.	
С	27, 28		3.13.11	The supernatant is allowed to warm to room temperature about 20 to 30 minutes.	
K	27, 28		3.13.12	The autoclaved soft agar is tempered and held at $51 \pm 1^{\circ}$ C throughout the period of sample analysis.	
K	27, 28		3.13.13	Two hundred microliters (0.2 mL) of log phase host strain <i>E coli</i> is added to the tempering soft agar immediately prior to adding the sample supernatant.	
K	27, 28		3.13.14	The sample supernatant is shaken or vortexed before being added to the tempering soft agar.	
С	27, 28		3.13.15	2.5 mL of sample supernatant is added to each tube of tempering soft agar.	
С	27, 28		3.13.16	The soft agar/sample supernatant/host cell mixture is gently rolled between the palms of the hands to mix.	
С	27, 28		3.13.17	The soft agar/sample supernatant/host cell mixture is overlaid onto bottom agar plates and swirled gently to distribute the mixture evenly over the plate.	
С	28		3.13.18	Ten (10) plates are used, 2.5 mL per plate for a total of 25 mL of supernatant analyzed per sample.	
K	27, 28		3.13.19	Negative and positive control plates are prepared and accompany each set of samples analyzed. The results are recorded and records maintained. Positive control	
K	27, 28		3.13.20	Growth broth is used as the negative control or blank.	
K	27, 28		3.13.21	Type strain MS2 (ATCC 15597) male specific bacteriophage appropriately diluted to provide countable low levels of phage is used as the positive control.	
K	2		3.13.22	A negative control plate is plated at the beginning and end of each set of samples analyzed.	
K	27, 28			The positive control is plated after all the samples are inoculated and immediately prior to the final negative control.	
С	27, 28		3.13.24	All plates are incubated at $36 \pm 1^{\circ}$ C for 18 ± 2 hours.	
		3.14 C	omputat	ion of Results - MSC	
С	27		3.14.1	Circular zones of clearing or plaques of any diameter in the lawn of host bacteria are counted.	
С	28, 32		3.14.2	The working range of the method is 1 to 200 PFU per plate. When there are no plaques on all ten plates, the count is <6 PFU/100 grams for soft-shelled clams, <7 PFU/ 100 grams for American oysters, and <5 PFU/ 100 grams for quahog (hard) clams. If the density exceeds 200 PFU per plate on all plates, the count is given as > 20,000 PFU/100 grams.	
K	28		3.14.3	The formula used for determining the density of MSC in PFU/100 grams is: (0.364) (N) (Ws), where N = total number of plaques counted on all 10 plates and Ws = weight of the supernatant used.	
0	9		3.14.4	The MSC count is rounded off conventionally to give a whole number.	

REFERENCES

- 1. American Public Health Association 1984. *Compendium of Methods for the Microbiological Examination of Foods*, 2nd Edition. APHA, Washington, D.C.
- 2. Good Laboratory Practice.
- 3. "Interim Guides for the Depuration of the Northern Quahog, *Mercenaria mercenaria*." 1968. Northeast Marine Health Sciences Laboratory, North Kingstown, RI.

- 4. U.S. Department of Commerce. 1976. NBS *Monograph 150*. U.S. Department of Commerce, Washington, D.C.
- 5. Association of Official Analytical Chemists (AOAC). Current Edition. *Official Methods of Analyses of the Association of Official Analytical Chemists*. Official method 978.23. Chapter 17.305. AOAC Arlington, VA.
- 6. Wilt, D.S. (ed.). 1974. *Proceedings of the* 8th *National Shellfish Sanitation Workshop*. U.S. Food and Drug Administration, Washington, D.C.
- 7. U.S. Public Health Service (PHS). 1947. Public Health Report, Reprint #1621. PHS, Washington, D.C.
- 8. Association of Official Analytical Chemists (AOAC). 1991. *Quality Assurance Principles for Analytical Laboratories*. AOAC, Arlington, VA.
- 9. American Public Health Association (APHA). 1970. *Recommended Procedures for the Examination of Sea Water and Shellfish*, 4th Edition. APHA, Washington, D.C.
- 10. Interstate Shellfish Sanitation Conference (ISSC). 1986. *Shellfish Sanitation Interpretation #SS-39*. ISSC, Columbia, S.C.
- 11. American Public Health Association (APHA). 1992. *Standard Methods for the Examination of Water and Wastewater*, 18th Edition. APHA/AWWA/WEF, Washington, D.C.
- 12. Title 21, Code of Federal Regulations, Part 58, *Good Laboratory Practice for Nonclinical Laboratory Study*. U.S. Government Printing, Washington, D.C.
- 13. American Public Health Association (APHA). 1992. *Standard Methods for the Examination of Dairy Products*, 16th Edition. APHA, Washington, D.C.
- 14. Fisher, J. 1985. Measurement of pH. American Laboratory 16:54-60.
- 15. Consult pH electrode product literature.
- 16. Association of Official Analytical Chemists (AOAC). 1999. AOAC Methods Validation and Technical Programs - Criteria for Laboratories Performing Food Testing. AOAC, Arlington, VA.
- 17. U.S. Environmental Protection Agency (EPA). 1975. *Handbook for Evaluating Water Bacteriological Laboratories*. EPA-670/9-75-006. U.S. EPA, Cincinnati, OH
- 18. Adams, W.N. 1974. NETSU. Personal communication to Dr. Wallace Andrews, FDA.
- 19. U.S. Food and Drug Administration (FDA).1995.*Bacteriological Analytical Manual*. U.S. FDA, 8th Edition, AOAC, Arlington, VA.
- 20. U.S. Food and Drug Administration (FDA) and Interstate Shellfish Sanitation Conference (ISSC). 1997. *NSSP Guide to the Control of Molluscan Shellfish*. FDA/ISSC, Washington, D.C. and Columbia, S.C.
- 21. U.S. Environmental Protection Agency. 1978. *Microbiological Methods for Monitoring the Environment, Water and Wastes*. EPA/600/8/78/017. EPA, Washington, D.C.
- 22. Furfari, Santo. March 21, 1972. Personal Communication to Dan Hunt, FDA.
- 23. United States Environmental Protection Agency, *Improved Enumeration Methods for the Recreational Water Quality Indicators: Enterococci and Escherichia coli*. EPA/821/R-97-004, EPA, Washington, DC
- 24. Rippey, Scott, R, Adams, Willard, N, and Watkins, William, D. Enumeration of fecal coliforms and *E. coli* in marine and estuarine waters: an alternative to the APHA-MPN approach, Journal WPCF, 59, 8 (1987).
- 25. FDA Manual of Interpretations, National Shellfish Sanitation Program *Guide for the Control of Molluscan Shellfish*, 2003 Revision, Interpretation Number 03-IV-@.02-102.
- 26. *Membrane filtration: A Users Guide and Reference Manual*, Thomas D. Brock, Science Tech Inc., Madison, WI, 1983.
- 27. Proceedings of the Male-specific Bacteriophage (MSC) Workshop, Gloucester, MA, March 9-12, 2004.
- 28. MSC Method and SLV write-up, Proposal 05-114 Spinney Creek Shellfish, Inc., September, 2009.
- 29. American Public Health Association. 1970. *Recommended Procedures for the Examination of Sea Water and Shellfish*, 4th Edition, APHA, New York, N.Y.
- 30. ASTM Manual on the Use of Thermocouples in Temperature Measurement, MNL-12 (ASTM, West Conshohocken, PA, 1993).
- 31. JOHN KAROLUS, MERCURIA CUMBO, SUSAN BOEHLER, and LAURA SAVINA. Modification of an Approved Medium for Fecal Coliform Detection in Seawater: A-1 Medium Minus Salicin. *Journal of Food Protection*: Vol. 66, No. 1, pp. 120–121.
- 32. MSC Method and SLV write-up, Proposal 13-120 Spinney Creek Shellfish, Inc., January, 2014.

SHELLFISH LABORATORY EVALUATION CHECKLIST

SUMMARY OF NONCONFORMITIES

Item	Observation	Documentation Required Image: Constraint of the second s
	1 1	
	Г 	
		I
		I

LAB	ORA	TORY STATUS			1		
LAB	ORA	TORY			DATE		
LAB	ORA	TORY REPRESEN	ГАТІVЕ:				
			PONENT: (Part I-III)				
A. Re	esults						
Total	# of (Critical (C) Nonconfo	ormities in Parts I-III				
Total	# of]	Key (K) Nonconform	ities in Parts I-III				
Total	# of (Critical, Key and Oth	er (O)				
Nonc	onfor	mities in Parts I-III					
B.	Crit	teria for Determinin	g Laboratory Status of the Mi	crobiolog	gical Component:		
	of this laboratory is not in conformity with						
		a. The total # of Cri	tical nonconformities is \geq 4 or				
		b. The total # of Ke	y nonconformities is \geq 13 or				
		c. The total # of Cri	tical, Key and Other is ≥ 18				
2. Provisionally Conforms Status: The microbiological component of this laboratory is determined provisionally conforming to NSSP requirements if the number of critical nonconformities is ≥ 1 by							
C.	Lab	oratory Status (<i>circl</i>	e appropriate)				
	Doe	s Not Conform	Provisionally Conforms	(Conforms		
Ackn	owled	Igment by Laboratory	Director/Supervisor:				
			plemented and verifying substan		ocumentation received by the Laboratory 		
Laboi	ratory	Signature:			Date:		
LEO	LEO Signature: Date:						

NSSP Form LAB-100 Microbiology Rev. October 2015